

7056 Acrylic Core Tape



Product Description

Tesa 7056 is an acrylic core tape with an acrylic adhesive offering good adhesion, good stress dissipation and good resistance to temperatures and weather. It is suitable for constructive bonding to transparent and translucent materials. Its acrylic core compensates for different thermal elongation of bonded parts. Available with various liners in clear polyester, blue film or white paper with or without branding.

Main Applications

- Partition walls
- Sign manufacturing industry
- Deco glass panels industry

Technical data

	Metric	Imperial
Thickness	2 mm	60 mil
Adhesion to steel	27 N/cm	246.7 oz/in
Elongation at Break	1000%	1000%
Operating Temperature	≤100 °C	≤212 °F
Long Term Temperature Resistance	100 °C	212 °F
Short Term Temperature Resistance	200 °C	392 °F

Backing

Solid acrylic

Type of Adhesive

Pure acrylic

Liner

Yes

Colour



Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.