

330X Aluminum Foil Tape



Product Description

330X is an extreme weather foil tape with an aluminum backing and a high performance acrylic adhesive. It is conformable and resistant to UV, moisture and mold. It also offers a low VOC content, a high tack, an aggressive bond as well as an excellent performance in extreme weather. This tape meets flammability requirements for construction, aerospace and marine applications.

Main Applications

- Insulation seaming and patching
- Refrigeration applications
- General purpose industrial and automotive uses
- Aircraft sealing and masking
- Window mask
- Taping joints and seams

Technical data

	Metric	Imperial
Thickness	89 µm	3.5 mil
Adhesion to steel	6.0 N/cm	55 oz/in
Tensile Strength	25 N/cm	14 lb/in
Application Temperature	≥-32 °C	≥-25 °F
Operating Temperature	-37 to 127 °C	-35 to 260 °F
Long Term Temperature Resistance	127 °C	260 °F

Backing

Aluminum foil

Type of Adhesive

Acrylic

Liner

Unbleached kraft paper

Colour



Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.