

360 Aluminum Foil Tape



Product Description

360 is a heavy duty foil tape with a conformable aluminum backing and an aggressive butyl mastic adhesive. It offers a low VOC Content, an instant water and air-tight seal and resistance to moisture and solvents. It also conforms to round, square and odd shaped objects.

Main Applications

- Duct joint sealing for low, medium and high pressure HVAC systems
- Permanent repairs
- Repairs in aluminum siding, sheet metal, gutters and more

Technical data

	Metric	Imperial
Thickness	432 µm	17 mil
Adhesion to steel	22 N/cm	200 oz/in
Tensile Strength	35 N/cm	20 lb/in
Operating Temperature	4 to 93 °C	40 to 200 °F
Long Term Temperature Resistance	93 °C	200 °F

Backing

Aluminum foil

Type of Adhesive

Butyl rubber

Liner

Blue LDPE

Colour



Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.