1716W
Foam Tape

Product Description

1716W is a double coated conformable polyethylene designed for general purpose bonding applications. Its aggressive rubber adhesive bonds to most surfaces including low energy materials such as polyethylene and polypropylene.

Main Applications

- General purpose mounting, gasketing and sealing applications
- Gap filling function in joining uneven or irregular surfaces
- Price channel attachment
- Metal shelf signage

Technical data

	Metric	Imperial
Thickness	2 mm	62 mil
Adhesion to steel	15 N/cm	137 oz/in
Elongation at Break	339%	339%
Tensile Strength	254 N/cm	145 lb/in
Operating Temperature	≤116 °C	≤240 °F
Long Term Temperature Resistance	116 °C	240 °F

Backing

PE foam

Type of Adhesive

Rubber

Liner

Yes

Colour

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.