

530 Flatback Tape



Product Description

530 is a pressure sensitive flatback tape with synthetic and natural rubber adhesive. It performs well in different temperatures and humidity conditions. It is also suitable for reduced weight applications to provide packaging material savings. It complies with postal regulations for uninsured packages. It is not repulpable.

Main Applications

- Carton sealing and packaging
- Silk screening
- Picture framing
- Beaming/leasing
- Splicing
- Tabbing

Technical data

	Metric	Imperial
Thickness	185 µm	7.3 mil
Adhesion to steel	6.3 N/cm	58 oz/in
Elongation at Break	7%	7%
Tensile Strength	70 N/cm	40 lb/in
Operating Temperature	4 to 79 °C	40 to 175 °F
Long Term Temperature Resistance	79 °C	175 °F

Backing

Kraft flatback

Type of Adhesive

Natural/synthetic rubber

Colour



Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.