30LXUB-1618
Surface Protection Film

Product Description

30LXUB-1618is a high tack protective masking film consisting of a blended polyethylene self-wound carrier and a custom formulated water based adhesive. This film offers up to 12 months UV resistance. The protective film provides abrasion, tear and puncture resistance and is suitable for interior and exterior applications.

Main Applications

- Masking and protection of textured surfaces
- Long term exterior protection from UV and environmental elements
- Window masking
- Protection of painted or polished metals and anodized aluminum

Technical data

	Metric	Imperial
Thickness	76 µm	3 mil
Adhesion to steel	1.8 to 2.0 N/cm	16 to 18 oz/in
Elongation at Break	450%	450%
Tensile Strength	8750 N/cm	5000 lb/in

Backing

Blended PE film

Type of Adhesive

Water based acrylic

Colour

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.