

# 6329S Polyethylene Tape



## Product Description

6329S has a heavy-duty polyethylene backing with synthetic rubber adhesive. It bonds well to most surfaces in a wide range of temperatures. It is also conformable and hand tearable. It is able to maintain a watertight seal and is excellent in low-temperature bonding.

## Main Applications

- Wire identification
- Surface protection
- Polyethylene splicing
- Anti-corrosion barrier for dissimilar metals
- Shrink wrap applications

## Technical data

	Metric	Imperial
Thickness	229 µm	9 mil
Adhesion to steel	7.7 N/cm	70 oz/in
Elongation at Break	100%	100%
Tensile Strength	39 N/cm	22 lb/in
Application Temperature	18 °C	65 °F

## Backing

PE film

## Type of Adhesive

Synthetic rubber

## Colour



Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.