75505
Double Coated Tape

Product Description

tesa® 75505 is a conformable, tackified acrylic transfer tape with a transparent, age-resistant, high tack adhesive. It offers a very good initial hold on uneven surfaces, very good resistance to temperature and humidity, good die-cutting properties and excellent conformability.

Main Applications

- Mounting of lightweight parts and materials
- Mounting of foams, felts, fabrics and textiles
- Lamination of insulation materials
- Mounting of flooring systems
- Membrane switch mounting
- Splicing

Technical Data

	Metric	Imperial Units
Thickness	50 µm	1.97 mil
Adhesion to Steel	8 N/cm	73.09 oz/in
Long Term Temperature Resistance	100 °C	212 °F
Short Term Temperature Resistance	200 °C	392 °F

Backing
None

Type of adhesive
Tackified acrylic

Liner
Glassine

Colour
Transparent

Colour of liner
Brown / blue logo

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.