

1220C Acrylic Core Tape



Product Description

1220C is an acrylic core tape designed for constructive and permanent bonding of transparent materials. Its acrylic core compensates for different thermal elongation of bonded parts, ensuring durability and stability. It also offers a high immediate tack and peel adhesion, making it ideal for various applications.

Main Applications

- Glass partition wall assembly
- Bonding of transparent and translucent materials
- Sign manufacturing industry
- Deco glass panels industry
- General mounting requiring water- and dust-proof bond

Technical data

	Metric	Imperial
Thickness	500.58 µm	19.7 mil
Adhesion to Steel	10 N/cm	91.3 oz/in
Long Term Temperature Resistance	80 °C	176 °F
Short Term Temperature Resistance	120 °C	248 °F

Backing

Acrylic foam

Adhesive Type

Acrylic

Liner

Red Filmic

Colour



Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

