

# PLATE MOUNTING SOLUTIONS

For Flexible Packaging Printing



neXt Level performance throughout the whole proccess

With **tesa® Softprint neXt**, you can achieve the process efficiency you seek—saving valuable time during tape and plate mounting and demounting, minimizing machine downtime during printing, and preventing plate damage upon demounting, ensuring they remain ready for future use. This translates to significant time and cost savings.

### **X** During Mounting...

The low-tack plate-side adhesive allows for easy plate repositioning until pressure is applied, creating a firm bond.

## **X** During Printing...


The high-performance adhesive prevents plate edge lifting, enhancing print quality, improving overall efficiency, and reducing waste.

## **X** During Demounting...

The plate-side adhesive allows for smooth demounting, regardless of the print run length, plate condition, or cleaning process, preventing any damage to the printing plate.

## tesa® Softprint neXt

What may seem like contradicting properties can now be achieved with tesa® Softprint neXt. Maintaining the trusted mounting and secure bonding properties, the plate-side adhesive has now been improved to ensure the easiest demounting processes.





					<b>***</b>	
Product line	<b>Product Design</b>	 				
tesa Sofprint® <b>FE neXt</b>	Flex	 73422NXT	73524NXT	73526NXT		
tesa Sofprint® <b>FE-X neXt</b>	Flex	 73522NXT	73524NXT	73526NXT		
tesa Sofprint® FE-X neXt EA(1)	Flex	73522NXT EA	73524NXT EA	73526NXT EA	73528NXT EA	

MEDIUM

HARD-MEDIUM

<sup>1.</sup> tesa® Softprint easy application (EA) liner for extra smooth mounting: The structured liner creates micro channels in the adhesive to avoid air accumulation beneath the plate during the mounting and printing process. Available for selected products.



X-HARD

## Our complementary products for flexographic printing

#### **Roller Wrapping**

Product	Solution
4863	Anti-slip silicone tape with embossed surface
4563	Anti-slip silicone tape with smooth surface
PTFE Tape	Nonstick surface—low coefficient of friction makes it very slick

#### **Core Starting**

Product	Solution
2901	Double-sided tape with excellent adhesion and excellent resistance to oils
64620	Double-sided tape is solvent free and high tack
51194	Splittable double-sided tape for flying splice labelling
51904	Double-sided tape with high tack and adhesion
RW 294	Reverse wound transfer tape with good adhesion and godd shear properties
RW 699	Reverse wound transfer tape with good adhesion and godd shear properties

#### **Edge Sealing**

Product	Solution	
60762	Single-sided tape with high conformability and good abrasion resistance	
6032	Single-sided tape for safe bond on a variety of materials	
4244	Single-sided tape with high flexibility	

#### **Splicing**

Product	Solution	
51910	No need for scissors or cutters	
51918	Secure splice performance on: thick films, Sharp edge films &Tubular bags	
51948	Secure splice performance even at high speeds	
61958	Secure splice performance on standard films	



#### mpi-matco.com