

5310 Duct Tape



Product Description

5310 is a PE coated cloth tape equipped with an aggressive natural rubber adhesive. It offers high tensile strength, excellent tearability and superior holding power on rough or irregular surfaces. It removes cleanly from most surfaces for up to 30 days without residue. It is UV resistant and has a low VOC content, meets UL723, and is eligible for LEED® compliance credits.

Main Applications

- Outdoor masking wood, metal and concrete
- General repair
- Hanging PE sheeting or kraft paper for outdoor stucco installations

Technical data

	Metric	Imperial
Thickness	254 µm	10 mil
Adhesion to steel	5.5 N/cm	50 oz/in
Tensile Strength	39 N/cm	22 lb/in
Operating Temperature	4 to 93 °C	40 to 200 °F
Long Term Temperature Resistance	93 °C	200 °F

Backing

Cloth

Type of Adhesive

Natural rubber

Colour



Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.