

30LXUBW-6008

Surface Protection



Product Description

30LXUBW-6008 is a medium tack protective film consisting of a black and white co-extruded polyethylene self-wound backing and a water-based acrylic adhesive. It provides abrasion, tear and puncture resistance, while allowing clean and easy removal from most smooth and clean surfaces. The film offers up to 6 months of UV resistance. It is suitable for both interior and exterior applications.

Main Applications

- Masking and protection of smooth solid surfaces such as glass and marble
- Protection of polycarbonate and acrylic sheeting
- Window masking
- Protection of painted or polished metals and anodized aluminum
- Protection of unpainted and painted PVC extrusions

Technical data

	Metric	Imperial
Thickness	76 µm	3 mils
Adhesion to Steel	0.7 to 0.9 N/cm	6 to 8 oz/in
Tensile Strength	21 N/cm	12 lb/in
Elongation at break	325%	325%

Backing

LDPE/LLDPE film

Adhesive Type

Water based Acrylic

Colour

Black (adhesive side) / White (non-adhesive side)

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

