

7030 Printed Tape



Product Description

7030 is a premium packaging tape with a PVC-film backing and a natural rubber adhesive. Its PVC backing allows for a quiet unwind with greater tear and puncture resistance. It offers excellent performance on most types of cardboards and secures a safe closure. The natural rubber adhesive system is designed to show best results for applications on different kinds of surfaces. Foreground text and images can be printed in one or two colours on a single background colour. Standard tape colours are white, clear and tan, and custom background colours are also available.

Main Applications

- Applications at room temperatures and then stored in low temperature environments.
- Carton sealing
- Bundling
- Secure packaging
- Identification of contents and handling instructions
- Logos and branding

Technical data

	Metric	Imperial
Thickness	38 µm	1.5 mil
Adhesion to steel	23 N/cm	210 oz/in
Tensile strength	114 N/cm	65 lb/in
Elongation at break	55%	55%
Application Temperature	2 to 66 °C	35 to 150 °F
Operating Temperature	-17 to 82 °C	2 to 180 °F

Backing

UPVC

Adhesive Type

Natural Rubber

Colour

Clear, white and tan

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

