

2112

Masking Tape



Product Description

2112 is a premium-grade masking tape designed for critical paint masking applications. It features a high-adhesion rubber adhesive and a lightly creped paper backing with a heavier construction. The tape resists wet sanding and solvents and withstands temperatures up to 90°C / 194°F for 60 minutes or 120°C / 248°F for 30 minutes. The backing provides excellent conformability to curves and contours while maintaining excellent mechanical resistance. The tape offers good hand tearability and removes cleanly without leaving adhesive residue. Its orange colour provides good visibility during masking, and its 3-day UV resistance allows for short-term outdoor masking applications.

Main Applications

- Automotive painting
- Marine painting
- Truck and bus painting
- Spray booth painting
- Other critical paint masking applications

Technical data

	Metric	Imperial
Thickness	172.7 µm	6.8 mil
Tensile Strength	42.9 N/cm	24.5 lb/in
Elongation at break	9%	9%
Temperature Resistance — 60 minutes	90 °C	194 °F
Temperature Resistance — 30 minutes	120 °C	248 °F
Adhesion to Steel	2.02 N/cm	18.5 oz/in

Backing

Crepe paper

Adhesive Type

Rubber

Colour

Orange

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

