6502
Packaging Tape



Product Description

6502 is a general-purpose packaging tape used for carton sealing, splicing, bundling and other light- to medium-duty packaging applications. It is also suitable for colour coding and identification.

Main Applications

- Bundling
- Splicing
- Carton sealing
- Colour coding and identification

Technical Data

	Metric	Imperial
Thickness	25 µm	1 mil
Tensile Strength	39 N/cm	22 lb/in
Elongation at Break	165%	165%
Application Temperature	12 to 43 °C	54 to 110 °F
Operating Temperature	-1 to 60 °C	30 to 140 °F
Adhesion to Steel	4.2 N/cm	38 oz/in

Backing
BOPP Film

Adhesive Type
Synthetic Rubber

Colour
White, red, yellow, green, blue

Storage and Shelf Life: Unless otherwise specified, shelf life is one year from the date of manufacture when stored in the original packaging at approximately 22 °C (72 °F) and 50% relative humidity, away from direct sunlight. Contact MPI Matco to confirm any product-specific storage or shelf-life requirements.

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. MPI Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should perform their own tests to determine the suitability of the product for their intended application and shall assume all risks and liabilities in connection therewith.